

# BANGCHAK BRAKE FLUID 500

Fluids for Brake and Clutch Systems



**BANGCHAK BRAKE FLUID 500** is a premium brake fluid for use in all type of brake and hydraulic clutch systems. The boiling point is above 500 °F. for maximum driving performance.

The **FEATURES** are :

- o Increased safety through minimized drop in boiling point.
- o Will not damage the rubber components and corrode the metal parts in the brake system.
- o Fully compatible and miscible with other brake fluids of similar specification.

## MEET REQUIREMENT

- o FMVSS 116 Grade DOT 4 and DOT 3
- o SAE J-1703f
- o TISI 591-2528

## APPLICATION

BANGCHAK BRAKE FLUID 500 is suitable for passenger car, truck, bus and motorcycles.

## TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK BRAKE FLUID 500
Color, ASTM		Report
Eq. Reflux Boiling Point, °C	SAE J 1703	255 Min
Wet Boiling Point, °C	SAE J 1703	165 Min
pH	SAE J 1703	7.0-11.5
Density, g/cm <sup>3</sup>	SAE J 1703	1.010-1.055
Viscosity @ 100 °C, cSt.	SAE J 1703	1.5 Min

**Caution :** Brake fluid can damage vehicle paintwork and it must be immediately. It is also necessary to keep the container tight to avoid absorption of moisture. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs.

Packaging : 0.5 Litre, 1 Litre, 200 Litres

## FEATURES & BENEFITS



Brake Shield



Steady Boiling Point