

# BANGCHAK TORQUE FLUID

Multi-Purpose Hydraulic Fluids



**BANGCHAK TORQUE FLUID** is a premium universal lubricant for the hydraulic system, transmission, axles and wet-brake of tractors. It is blended from high quality base stock with additives to improve oxidation stability and formulated for long service under severe conditions. These included the following properties.

- o Excellent load-carrying capacity and wear protection.
- o Providing superior gear performance.
- o Good resistance to foaming.

## MEET REQUIREMENT

- o John Deere
- o Ford
- o Massey-Ferguson (Farm Equipment)
- o Allison C-4
- o Caterpillar TO-2
- o Sperry Vickers I-286-S & M-2950-S
- o Denison HF 0,1,2
- o Cincatti Milacron P68 , P69 , P70

## APPLICATION


BANGCHAK TORQUE FLUID can use in John deere, Massey-Ferguson and Ford New Holland tractors and recommended for use in all other makes of farm equipment. BANGCHAK TORQUE FLUID can use in equipment requiring Allison C-4 and Caterpillar TO-2 performance.

## TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK TORQUE FLUID	
			ISO 68
Appearance	Visual		Bright & Clear
Color	ASTM D1500		Report
Density @ 15 °C, g/cm <sup>3</sup>	ASTM D1298		Report
Flash Point (COC), °C	ASTM D92		220 Min
Foam Test (Seq II), mL	ASTM D892		50/0 Max
Pour Point, °C	ASTM D97		-6 Max
Kinematic Viscosity @ 40 °C, cSt.	ASTM D445		66.0-72.0
Viscosity Index	ASTM D2270		95 Min
Copper Strip	ASTM D130		1B Max

Packaging : 200 Litre

## FEATURES & BENEFITS



Efficiency  
Hydraulic System



Gear Protection