BANGCHAK HYDRAULIC 10W

Automotive Hydraulic Oil





BANGCHAK HYDRAULIC 10W is a hydraulic oil for automotive vehicles. Blended from high quality base oils and additives to meet the performance of API CF/SF standard. power It has the properties in transmission, anti-wear, anti-rust, anti-oxidation enable the hydraulic system to operate under severe conditions without adverse effects.

- o Excellent wear protection
- o Providing superior gear performance
- o Good resistance to foaming

MEET REQUIRMENT

o API CF/SF

APPLICATION


BANGCHAK HYDRAULIC 10W is commonly used with hydraulic system in various vehicles such as dump trucks, forklift trucks, crane trucks, tracktors, mobile hydraulic system and other heavy equipment. It can be used as a torque fluid in the hydraulic transmission system of heavy- equipments and also in the power-assisted steering units. It is suitable for diesel and gasoline engine where oil type and viscosity are appropriate.

TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK HYDRALIC 10W
Appearance	Visual	Bright & Clear
Color	ASTM D1500	Report
Density @ 15 °C, g/cm3	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	215 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max
Pour Point, °C	ASTM D97	-6 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	6.0-7.0
Viscosity Index	ASTM D2270	95 Min
Water Content, %Vol	ASTM D95	NIL
TBN, mg KOH/g	ASTM D2896	9.6 Min

Packaging: 5 Litres 200 Litres

FEATURES & BENEFITS



Additional Information Available at www.bangchaklubricants.com

Bangchak Corporation Public Company Limited. 2098 M Tower Building, Sukhumvit Road, Phrakanong, Bangkok, Thailand

SD-PD-02/1-15 REV. NO.: 08, DATE: 01/01/2023