FURIO SUPER GEAR GL-5

Multifunctional Gear Oil





FURIO SUPER GEAR GL-5 is a multipurpose extreme pressure gear oil. It is designed to give excellent performance for all heavy-duty equipment and resulted from applying high quality base oil with special additives. The benefits of FURIO SUPER GEAR GL-5 include outstanding results in high load pressure operations, protected against corrosion, reduced gear wear.

MEET REQUIRMENT

- o API GL-5
- o ZF TE-ML 07A
- o ZF TE-ML 08

APPLICATION

o FURIO SUPER GEAR GL-5 is a multipurpose extreme pressure gear oil meeting API GL-5 and has been used in most transmission, rear axels, differentials and gear units of automotives and off - highway mobile equipments. It is especially suitable for hypoid, limited slip and spiral-bevel gears. It can also be used in some steering gears and universal joints lubricated by oil.

TYPICAL INSPECTION

PROPERTIES	Method	FURIO SUPER GEAR GL-5	
		SAE 80W-90	SAE 85W-140
Appearance	Visual	Bright & Clear	Bright & Clear
Color	ASTM D1500	Report	Report
Density @ 15 °C, g/cm3	ASTM D4052	Report	Report
Flash Point (COC), °C	ASTM D92	215 Min	215 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max	50/0 Max
Pour Point, °C	ASTM D97	-18 Max	-18 Max
Kinematic Viscosity @ 100 oC, cSt.	ASTM D445	14.0-15.0	27.0-28.0
Viscosity Index	ASTM D2270	95 Min	95 Min

Packaging: 1 Litres, 5 Litres

FEATURE & BENEFITS



Gear Protection



Strong Oil Film



Heat Resistance