

BANGCHAK GREEN FLUSH

Low Viscosity Engine Flushing Oil



BANGCHAK GREEN FLUSH is a low viscosity high quality oil designed to flush out sludge and carbon deposits from both gasoline and diesel engine including industrial machine.

- o Effective deposit removal
- o Automotive engine and machinery applicable
- o Compatible with previous engine oil or industrial lubricants

APPLICATION

After drain crankcase oil or machinery lubricating oil, fill with BANGCHAK GREEN FLUSH and run engine/machinery without load for 5-10 minutes. Then drain flushing oil out. Finally add normal crankcase oil or machinery lubricating oil and run equipment as usual.

TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK GREEN FLUSH
Appearance	Visual	Bright & Clear
Color	ASTM D1500	Report
Density @ 15 °C, g/cm ³	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	205 Min
Pour Point, °C	ASTM D97	-6 Max
Kinematic Viscosity @ 40 °C, cSt.	ASTM D445	26-35
Viscosity Index	ASTM D2270	95 Min

Packaging : 18 Litre 200 Litre


FEATURES & BENEFITS



Superior Clean



High Quality Oil



Automotive and Industrial application