

# BANGCHAK COOLANT READY MIX

Summer Coolant



**BANGCHAK COOLANT READY MIX** is nitrites free coolant that contains ethylene glycol diluted with water and ready to use. Aqueous solution of it act both as excellent antifreeze and coolant and impart very good anticorrosion protection to all metal parts found in the cooling systems of internal combustion engines.

The benefits include:

- o An Effective Heat Transfer Fluid
- o Capable of Protecting Metals Against Corrosion
- o Reduces Evaporation Losses
- o Reduce Water Pump Cavitation

## MEET REQUIREMENT

- o ASTM D 3306

## APPLICATION

**BANGCHAK COOLANT READY MIX** is suitable for the cooling system of engines. It is suitable for all vehicle using coolant in radiator such as car, bus, truck and etc.

## TYPICAL INSPECTION

PROPERTIES	Method	COOLANT READY MIX
Appearance	Visual	Bright&Clear
Color		Green
Density @ 15.6°C, g/cm <sup>3</sup>	ASTM D1122	1.00-1.10
Freezing Point, 30% in diluted water, °C	ASTM D1177	- 30 Max
Boiling Point,		
- Boiling Point, 30% in diluted water, °C	ASTM D1120	103 Min
pH, 30% Vol, in distill water	ASTM D1287	7.5-9.5
Effect on Automotive Finish	ASTM D1882	No Effect


## FEATURES & BENEFITS



Overheat Secure



Anti-rust



Excellent Heat Transfer



Ready to use

Packaging : 1 Litre & 18 Litres

Caution : Summer coolant can damage vehicle paintwork and it must be washed off with water immediately. It is also necessary to keep the container tightly sealed to prevent absorption of moisture.

Contamination with dirt, water, petroleum products or other materials may result in coolant failure or costly repairs.