BANGCHAK D3 LONG LIFE



Premium Diesel Engine Lubricant



BANGCHAK D3 LONG LIFE is a heavy duty diesel engine oil for high performance vehicle such as bus trailer and truck. It is the highest yet in protection and bearing corrosion

control technology with API CI-4 and API CI-4 plus. BANGCHAK D3 LONG LIFE have many advantage :

- o antifoam, antiwear (protect engine)
- o reduce soot (clean engine)
- o Helps extend oil drain interval (-60,000 km)
- o Improve washing and cleaning properties to clean piston and piston ring to make highest power
- o Special additive to protect valve wear, piston deposit and reduce soot to make engine clean

MEET REQUIRMENT

o API CI-4, CI-4 plus o Caterpillar ECF-1 o DD93K215 o DD93K218 o Mack EO-N PP '03 o CES 20078 o MB 228.6, 228.31 o VDS-3

APPLICATION

For bus, trailer, truck , high performance diesel engine with direct injection (DI) and commonrail (CDI) systems, diesel engine equipped wit turbo-charged amd EGR systems. Furhermore, It is applicable for the vehicle which install LPG / NGV / CNG.

TYPICAL INSPECTION

| PROPERTIES | METHOD | BANGCHAK D3 LONG LIFE |
|------------------------------------|------------|-----------------------|
| | | SAE 15W-40 |
| Appearance | Visual | Bright & Clear |
| Color | ASTM D1500 | Report |
| Density @ 15 °C, g/cm3 | ASTM D1298 | Report |
| Flash Point (COC), °C | ASTM D92 | 215 Min |
| Foam Test (Seq II), mL/mL | ASTM D892 | 50/0 Max |
| Pour Point, °C | ASTM D97 | -21 Max |
| Kinematic Viscosity @ 100 °C, cSt. | ASTM D445 | 15.5-16.5 |
| Viscosity Index | ASTM D2270 | 135 Min |
| Cold Cranking Simulator, cP | ASTM D5293 | 6600 Max, @ -20 °C |
| TBN, mg KOH/g | ASTM D2896 | 8.6 Min |
| Copper Strip Corrosion | ASTM D130 | 1B Max |

Packaging : 200 Litres





Engine Protection



Strong Oil Film



Prolong Engine Life



Superior Clean