BANGCHAK D3 MAX

Lubricant for Diesel Vehicles





BANGCHAK D3 MAX is the superior lubricating oil for heavy-duty diesel engines equipped with turbo-charged or super-charged. It is a multigrade oil which formulated to exceed API CF-4/SJ standard and give superior performance for all heavy-duty engines. The benefits of BANGCHAK D3 MAX include extended engine life, outstanding results in high temperature operations, protected engine wear and extended oil drain interval.

MEET REQUIRMENT

o API CF-4/SJ

APPLICATION

o BANGCHAK D3 MAX is designed for all heavy-duty diesel engines, truck, bus, tractor, pick up, fishing boat especially high speed diesel engine.

o It can also be used in general gasoline engines and gasoline engines with catalytic converter.

TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK D3 MAX SAE 20W-50
Appearance	Visual	Bright & Clear
Color	ASTM D1500	Report
Density @ 15 °C, g/cm3	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	215 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max
Pour Point, °C	ASTM D97	-15 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	18.5-19.5
Viscosity Index	ASTM D2270	120 Min
Cold Cranking Simulator	ASTM D2896	9100 Max, @ -15°C
TBN, mg KOH/g	ASTM D2896	8.0 Min

Packaging: 6 Litres

