

# BANGCHAK ATF DEXRON III

Automatic Transmission Fluid



**BANGCHAK ATF DEXRON III** is a high quality lubricant intended primarily for automatic transmission requirement. It results from applying high quality synthetic oil with special additives. BANGCHAK ATF DEXRON III has high viscosity index , high oxidation stability and low temperature characteristics. It also offers good corrosion protection, excellent antifoaming and air separation properties, as well as the required constant friction coefficients.

- o Helps smooth driving operation
- o Effective wear protection
- o High VI for high temperature use
- o Longer oil drain interval

## MEET REQUIREMENT

- o Dexron III
- o Allison C-4
- o CAT TO-2
- o MB 236.2
- o Ford M
- o Ford ESP-M2C166-H
- o Ford ESP-M2C138-CJ

## APPLICATION

BANGCHAK ATF DEXRON III is satisfied the service needs of most of the car equipped with hydraulic transmission and recommended for the power section of many types of power steering units. It is also applied for fluid coupling system in practically every branch of the industry.

## FEATURES & BENEFITS



Efficiency  
Power Steering



High VI

## TYPICAL INSPECTION

PROPERTIES	METHOD	ATF DEXRON III
Appearance	Visual	Bright & Clear
Color	Visual	Red
Density @ 15 °C, g/cm <sup>3</sup>	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	177 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	7.0-7.8
Viscosity Index	ASTM D2270	165 Min

Packaging : 1 and 200 Litres

Additional Information Available at [www.bangchaklubricants.com](http://www.bangchaklubricants.com)

Bangchak Corporation Public Company Limited, 2098 M Tower Building, Sukhumvit Road, Phrakonong, Bangkok, Thailand

SD-PD-02/1-60  
REV. NO. : 05 , DATE : 01/01/2023