

BANGCHAK ATF 1A

Automatic Transmission Fluid



BANGCHAK ATF 1A is a high quality lubricant intended primarily for automatic gear vehicles, power steering units and automatic transmission requirement. It results from applying high quality synthetic base oil with multifunctional additives.

BANGCHAK ATF 1A has high viscosity index, high oxidation stability and low temperature characteristics; It also offers good corrosion protection, excellent antifoaming and air separation properties, as well as the required constant friction coefficients.

MEET REQUIREMENT

- o JASO 1A
- o GM DEXRON III(H)
- o TOYOTA T-III, T-IV
- o FORD MERCON
- o HONDA ATF Z-1
- o NISSAN MATIC FLUID C, D, J, K
- o MAZDA M-III, M-V, F-1, S-1, N-1
- o ALLISON C3, C4
- o BMW LT71141, LA2634
- o ETL-8072B, 7045E

APPLICATION

- o Recommended for using in automatic gear vehicles such as Toyota, Ford, Honda, Isuzu, Nissan, Hyundai, Subaru, General Motors, Chrysler etc. (Please refer to the owners' manual for proper fluid requirements)
- o Recommended for using in the power section of many types of power steering units
- o Recommended for using in fluid coupling system in practically every branch of the industry

FEATURES & BENEFITS



Efficiency
Power Steering



High VI



New Technology

TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK ATF 1A
Appearance	Visual	Bright & Clear
Color	Visual	Red
Density @ 15 °C, g/cm ³	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	177 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	6.8-7.8
Viscosity Index	ASTM D2270	140 Min

Packaging : 1 Litre , 200 Litre