

BANGCHAK PRIMEX

General Purpose Lubricating and Process Oil



BANGCHAK PRIMEX is a premium quality, general purpose Paraffinic base oil. It has high viscosity index with good oxidation stability and good demulsibility. This product can be use as process oil for rubber industry which helps better solubility of raw material mixture. Furthermore, once through lubrication system also suitable with the product.

- o High quality Paraffinic oil
- o Better oxidation stability
- o Excellent once through lubrication
- o Light load operation
- o Rubber process oil

APPLICATION

BANGCHAK PRIMEX is highly recommended in once through lubrication system and machines such as gears, bearings where operating in light loads condition.

It is not recommended in using with worm gears, hypoid gears and textile spindles.


TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK PRIMEX									
		ISO 10	ISO 22	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150	ISO 220	ISO 320	ISO 460
Appearance	Visual	B&C	B&C	B&C	B&C	B&C	B&C	B&C	B&C	B&C	B&C
Color	ASTM D1500	Report	Report	Report	Report	Report	Report	Report	Report	Report	Report
Flash Point (COC), °C	ASTM D92	150 Min	170 Min	204 Min	220 Min	225 Min	237 Min	245 Min	270 Min	280 Min	282 Min
Pour Point, °C	ASTM D97	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max	-6 Max
Kinematic Viscosity @ 40 °C,	ASTM D445	9-11	20-24	25-35	44-50	66-72	95-105	135-165	200-240	300-340	Report
Kinematic Viscosity @ 100 °C,	ASTM D445	Report	Report	Report	Report	Report	Report	Report	Report	Report	30-35
Viscosity Index	ASTM D2270	95 Min	95 Min	95 Min	95 Min	95 Min	95 Min	95 Min	95 Min	95 Min	95 Min

FEATURE & BENEFITS



Lubrications



Process Oil

Packaging : PRIMEX 68,150 - 18 Litres , 200 Litres

PRIMEX 10,22,32,46,100,220,320,460 - 200 Litres