

BANGCHAK INDUSTRIAL GEAR OGL

Special Industrial Gear Oil



BANGCHAK INDUSTRIAL GEAR OGL is a high quality open gear oil composed of graphite, tackiness and extreme pressure additive to ensure maximum protection from severe high load operation. The special anti-wear additive plus heavy-loading properties are provided by the strength-film oil outcome. It is design for last long oil drain service life with low oil loss consumption.

- o Special design for open gear with high load condition
- o High performance wear and rust protection
- o Graphite as solid lubrication

APPLICATION

It fit for lubricating and heat transferring in open gear which in low rotation speed.

Applicable for anti-rust by coating on the metal surface.

TYPICAL INSPECTION

PROPERTIES	METHOD	INDUSTRIAL GEAR OGL		
		60	200	450
Appearance	Visual	Black	Black	Black
Viscosity @ 40 °C, cSt.	ASTM D445	1,350 Min	3,800 Min	9,000 Min
Viscosity@ 100 °C, cSt.	ASTM D445	60 Min	200 Min	450 Min
Flash Point, °C	ASTM D92	210 Min	200 Min	200 Min
Timken OK Load, Lbs	ASTM D2782	35 Min	50 Min	50 Min

Packaging : 180 Kilograms

FEATURE & BENEFITS



Gear Protection



Extreme Pressure