

BANGCHAK MOULD OIL 10

MOULD RELEASE AGENT



MOULD OIL 10 is a general purpose mould release oil. It is suitable on most formwork types giving an excellent surface finish. It helps minimize rework process and reduce loss.

- o Superior film surface
- o Easy release, less deposit
- o Smooth surface work
- o Easily miscible when dilute with water

APPLICATION

MOULD OIL 10 is designed to aid in the release of concrete from wood or metal forms and can be applied by spray-gun, roller or by brush.

MOULD OIL 10 should be diluted 1:3 - 1:7 in water.

FEATURE & BENEFITS



Smart Release

TYPICAL INSPECTION

PROPERTIES	METHOD	MOULD OIL 10
Appearance, Neat	Visual	Clear, Light Amber
Specific Gravity @ 30 °C	ASTM D1298	0.87-0.89
Emulsion Stability		
5% in 400 ppm Water CaCO ₃ (ml oil/ ml cream)	IP 263	Oil Max 0.1
pH (100 ppm Water CaCO ₃)		
2%	pH METER	8.8
10%	pH METER	9.1
Foaming (ml) (50 ml shaken for 15 S 20:1) (100 ppm Water CaCO ₃)		
Initial	IP 312	20
After 30 sec.	IP 312	2

Packaging: 200 Litres

Additional Information Available at www.bangchaklubricants.com

Bangchak Corporation Public Company Limited. 2098 M Tower Building, Sukhumvit Road, Phrakonong, Bangkok, Thailand

SD-PD-02/2-62
REV. NO. : 01 , DATE : 01/01/2023